



# DATA SHEET

## Filter media

Tetratex

### Tetratex

<b>Product code</b>	8214
<b>Appearance</b>	White
<b>Use</b>	Filter bags
<b>Composition</b>	100% polyester substrate with ePTFE membrane
<b>Area weight</b> (DIN 53884)	550 g/m <sup>2</sup>
<b>Thickness</b> (DIN 53885)	2.0 mm
<b>Air Permeability</b> (DIN 53887)	50–80 l/dm <sup>2</sup> /min @ 200 Pa
<b>Surface finish</b>	Microporous Tetratex® ePTFE membrane
<b>Additional treatments</b>	Heat set
<b>Surface electrical resistance</b> (DIN 54345)	N/A
<b>IFA/BIA certificate</b> (DIN 660335-2-69)	Class M Test report number: 201123625/6210
<b>Temperature (dry heat)*</b>	
Continuous	150 °C
<b>Chemical resistance</b>	
Hydrolysis	Poor
Acids	Good
Alkalis	Good
Oxidising agents	Very good
Organic solvents	Very good
<b>Abrasion resistance</b>	Excellent
<b>Supports combustion</b>	Yes
<b>Application field</b>	The microporous PTFE membrane gives improved filtration properties over conventional needlefelts, resulting in improved efficiencies and lower pressure drop, particularly when handling very fine or free-flowing and searching dusts.

\* Temperature limitations are for the media only and do not take other filter components into account